

非旋轉 4 股鋼纜

Non Rotating 4 Strand Wire Rope



U 4 x SeS (39)

結構：4 X 39 (F + 9 + 15 + 15) FC

用途：吊升起重

特性：1. 不旋轉性優 2. 極少變形 3. 耐磨性特強
4. 破斷載荷大 5. 柔軟性佳 6. 耐疲勞性高

直徑 Diameter				破斷荷重 (噸)			概算單位重量 Approximate Weight
鋼索 Rope		上層索線徑 Outer Wire Dia	斷面積 Metallic Area	Minimum Breaking Strength in Metric Tons			
mm	inch	mm	mm ²	A級	B級	特級	Kg/M
8	5/16	0.56	28.7	3.83	4.18	4.53	0.261
9	3/8	0.63	36.4	4.83	5.28	5.72	0.330
10	13/32	0.71	44.9	5.98	6.52	7.06	0.408
11.2	7/16	0.80	56.3	7.50	8.19	8.87	0.512
12	15/32	0.85	64.7	8.32	9.08	9.84	0.588
12.5	1/2	0.90	70.2	9.35	10.2	11.1	0.638
14	9/16	1.00	88.0	11.7	12.8	13.9	0.800
16	5/8	1.12	115	15.3	16.7	18.1	1.04
18	23/32	1.25	145	19.4	21.2	23.0	1.32
20	25/32	1.40	180	23.9	26.1	28.3	1.63
22	7/8	1.57	217	28.9	31.6	34.2	1.97
22.4	7/8	1.60	225	30.0	32.8	35.5	2.05
24	15/16	1.70	259	33.2	36.3	39.3	2.35
25	1	1.80	281	37.3	40.7	44.1	2.55
26	1 1/32	1.85	303	40.3	44.0	47.6	2.76
28	1 3/32	2.00	352	46.9	51.2	55.4	3.20
30	1 3/16	2.12	405	53.8	58.7	63.6	3.73
31.5	1 1/4	2.24	445	59.3	64.7	70.1	4.10
32	1 1/4	2.27	460	61.2	66.8	72.3	4.23
33.5	1 5/16	2.36	506	67.1	73.2	79.3	4.64
34	1 11/32	2.40	519	69.1	75.4	81.7	4.78
35.5	1 13/32	2.50	568	75.4	82.2	89.0	5.21
36	1 13/32	2.55	582	77.5	84.5	91.5	5.36
37.5	1 15/32	2.65	634	84.1	91.7	99.3	5.81
38	1 1/2	2.70	648	86.4	94.2	102	5.97
40	1 9/16	2.80	718	93.8	102	110	6.61
42	1 21/32	2.95	792	103	113	122	7.29
42.5	1 11/16	3.00	811	106	115	125	7.46
44	1 3/4	3.10	869	113	124	134	8.02
45	1 25/32	3.15	909	119	129	140	8.37