

# 不銹鋼鋼纜

## Stainless Steel Wire Rope



7 x 7



7 x 19

用途：航空及控制內線用

規格	直徑 Diameter			破斷荷重 (噸)		概算單位重量 Approximate Weight
	鋼索 Rope		鋼絲 Wire	Minimum Breaking Strength in Metric Tons		
	mm	inch		mm	SUS304	SUS305,316
7 x 7	1.5	1/16	0.16	0.162	0.143	0.010
	2	5/64	0.22	0.276	0.247	0.016
	2.5	3/32	0.27	0.437	0.380	0.027
	3	1/8	0.35	0.665	0.589	0.041
	4	5/32	0.44	1.08	0.988	0.068
	5	3/16	0.55	1.70	1.54	0.105
	6.3	1/4	0.70	2.59	2.34	0.160
	8	5/16	0.88	4.27	3.52	0.269
	9	3/8	1.00	5.34	4.22	0.341
	10	13/32	1.10	6.58	5.20	0.421
	11.2	7/16	1.24	7.41	5.86	0.474
	12	15/32	1.33	9.22	7.49	0.585
	12.5	1/2	1.39	9.63	7.83	0.611
	14	9/16	1.54	10.7	10.16	0.825
	16	5/8	1.78	16.0	13.1	1.08
	18	23/32	2.00	20.6	16.8	1.36
	20	25/32	2.20	24.7	20.0	1.68
	22	7/8	2.44	29.9	24.2	2.03
	22.4	7/8	2.48	30.7	25.0	2.10
	24	15/16	2.66	35.5	28.7	2.40
25	1	2.76	38.8	31.5	2.65	
7 x 19	4	5/32	0.26	1.06	0.892	0.066
	5	3/16	0.33	1.66	1.39	0.103
	6	1/4	0.40	2.35	2.04	0.151
	6.3	1/4	0.42	2.58	2.21	0.164
	8	5/16	0.53	3.97	3.42	0.261
	9	3/8	0.60	5.17	4.35	0.334
	10	13/32	0.66	6.12	5.17	0.412
	11.2	7/16	0.74	7.35	6.14	0.517
	12	15/32	0.80	8.47	7.06	0.594
	12.5	1/2	0.83	9.30	7.77	0.655
	14	9/16	0.93	11.3	9.40	0.819
	16	5/8	1.06	14.1	11.6	1.06
	18	23/32	1.19	17.7	14.7	1.34
	20	25/32	1.32	21.2	18.2	1.65
	22	7/8	1.45	25.7	22.0	2.00
	22.4	7/8	1.47	26.4	22.8	2.07
	24	15/16	1.58	30.6	26.2	2.37
	25	1	1.65	33.5	28.7	2.60
	26	1 1/32	1.70	35.5	30.3	2.74
	28	1 3/32	1.86	42.2	36.2	3.28
30	1 3/16	1.97	47.1	40.7	3.71	
32	1 1/4	2.11	52.8	44.9	4.22	