

# 鋼纜

## Wire Rope



6 x 24

結構：6撚 24線 7麻心

用途：船舶、漁業、起重機、營建重機械

直徑 Diameter		鋼絲 Wire	破斷荷重 (噸) Minimum Breaking Strength in Metric Tons		概算單位重量 Approximate Weight Kg/M
鋼索 Rope			G級	A級	
mm	inch	mm			
8	5/16	0.45	2.97	3.21	0.212
9	3/8	0.51	3.75	4.06	0.269
10	13/32	0.56	4.64	5.02	0.332
11.2	7/16	0.63	5.82	6.29	0.416
12	15/32	0.68	6.68	7.22	0.478
12.5	1/2	0.71	7.25	7.84	0.519
14	9/16	0.78	9.09	9.83	0.651
16	5/8	0.90	11.9	12.8	0.850
18	23/32	1.01	15.0	16.2	1.08
20	25/32	1.12	18.5	20.1	1.33
22	7/8	1.24	22.5	24.3	1.61
22.4	7/8	1.26	23.3	25.2	1.67
24	15/16	1.35	26.7	28.9	1.91
25	1	1.41	29.0	31.3	2.08
26	1 1/32	1.45	31.4	33.9	2.24
28	1 3/32	1.58	36.4	39.3	2.60
30	1 3/16	1.68	41.8	45.1	2.99
31.5	1 1/4	1.78	46.0	49.8	3.29
32	1 1/4	1.80	47.5	51.4	3.40
33.5	1 5/16	1.88	52.1	56.7	3.73
34	1 11/32	1.91	53.6	58.0	3.84
35.5	1 13/32	2.00	58.5	63.2	4.18
36	1 13/32	2.03	60.1	65.0	4.30
37.5	1 15/32	2.11	65.2	70.5	4.67
38	1 1/2	2.14	67.0	72.4	4.79
40	1 9/16	2.24	74.2	80.2	5.31
42	1 21/32	2.34	81.8	88.5	5.86
42.5	1 11/16	2.40	83.8	90.6	6.00
44	1 3/4	2.44	89.8	97.1	6.43
45	1 25/32	2.55	94.0	102	6.72
46	1 13/16	2.58	98.2	106	7.03
47.5	1 7/8	2.66	105	113	7.49
48	1 7/8	2.70	107	116	7.65
50	2	2.82	117	125	8.30
52	2 1/16	2.90	125	136	8.98
53	2 3/32	3.00	130	141	9.33
54	2 1/8	3.03	135	146	9.68