

鋼纜

Wire Rope



6 x 37

結構：6撚 37線 1麻心

用途：起重機、吊車、一般機械

直徑 Diameter			破斷荷重 (噸)			概算單位重量
鋼索 Rope		鋼絲 Wire	Minimum Breaking Strength in Metric Tons			Approximate Weight
mm	inch	mm	G級	A級	B級	Kg/M
6.3	1/4	0.3	1.98	2.15	2.29	0.143
8	5/16	0.38	3.19	3.46	3.69	0.230
9	3/8	0.43	4.04	4.38	4.67	0.291
10	13/32	0.47	4.99	5.41	5.76	0.359
11.2	7/16	0.53	6.26	6.79	7.23	0.451
12	15/32	0.57	7.19	7.79	8.29	0.517
12.5	1/2	0.60	7.80	8.45	9.00	0.561
14	9/16	0.66	9.81	10.6	11.3	0.704
16	5/8	0.76	12.7	13.8	14.7	0.920
18	23/32	0.85	16.2	17.5	18.7	1.16
20	25/32	0.94	19.9	21.6	23.0	1.44
22	7/8	1.04	24.2	26.2	27.9	1.74
22.4	7/8	1.06	25.0	27.1	28.9	1.80
24	15/16	1.14	28.7	31.2	33.2	2.07
25	1	1.19	31.2	33.8	36.0	2.25
26	1 1/32	1.22	33.7	36.6	38.9	2.43
28	1 3/32	1.33	39.0	42.4	45.2	2.82
30	1 3/16	1.41	44.8	48.7	51.8	3.23
31.5	1 1/4	1.50	49.5	53.7	57.2	3.57
32	1 1/4	1.52	51.1	55.4	59.0	3.68
33.5	1 5/16	1.58	56.0	60.7	64.6	4.03
34	1 11/32	1.63	57.0	62.5	66.6	4.15
35.5	1 13/32	1.68	62.9	68.2	72.6	4.53
36	1 13/32	1.70	64.7	70.1	74.6	4.66
37.5	1 15/32	1.78	70.2	76.1	81.0	5.05
38	1 1/2	1.80	72.1	78.1	83.2	5.19
40	1 9/16	1.88	79.7	86.6	92.2	5.75
42	1 21/32	2.00	88.0	95.4	102	6.34
42.5	1 11/16	2.03	90.1	97.7	104	6.49
44	1 3/4	2.11	96.6	105	112	6.96
45	1 25/32	2.14	101	110	117	7.28
46	1 13/16	2.20	106	114	122	7.60
47.5	1 7/8	2.24	113	122	130	8.11
48	1 7/8	2.30	115	125	133	8.28
50	2	2.37	125	135	144	8.98
52	2 1/16	2.48	135	146	156	9.72
53	2 3/32	2.51	140	152	162	10.1
54	2 1/8	2.58	146	158	168	10.5