


鍍鋅鋼絞線

Galvanized Steel Wire Strand



1 x 7



用途：架空地線、埋設地線、支線、電桿拉線等

通用抗拉強度等級為 70、90 及 125 kg/mm²

股線 Strand		單線 Wire	破斷荷重 (噸) Minimum Breaking Strength in Metric Tons										單位重量 Approx. Weight	
mm	inch		35 kg/mm ²	40 kg/mm ²	50 kg/mm ²	60 kg/mm ²	70 kg/mm ²	80 kg/mm ²	90 kg/mm ²	100 kg/mm ²	110 kg/mm ²	120 kg/mm ²	125 kg/mm ²	Kg/100M
3.0	1/8	1.0	0.174	0.200	0.250	0.300	0.349	0.399	0.449	0.499	0.552	0.602	0.621	4.43
3.6	9/64	1.2	0.249	0.286	0.356	0.427	0.499	0.570	0.641	0.712	0.796	0.860	0.888	6.32
4.2	5/32	1.4	0.340	0.390	0.485	0.582	0.680	0.776	0.873	0.970	1.07	1.17	1.20	8.63
4.8	3/16	1.6	0.443	0.509	0.633	0.760	0.885	1.02	1.14	1.26	1.40	1.52	1.57	11.25
5.4	7/32	1.8	0.558	0.645	0.800	0.960	1.12	1.28	1.44	1.60	1.77	1.93	1.99	14.22
6.0	1/4	2.0	0.693	0.794	0.989	1.18	1.39	1.58	1.78	1.98	2.18	2.37	2.47	17.52
6.9	9/32	2.3	0.915	1.05	1.31	1.57	1.83	2.09	2.36	2.61	2.87	3.14	3.27	23.17
7.8	5/16	2.6	1.17	1.34	1.67	2.01	2.34	2.68	3.01	3.35	3.69	4.01	4.18	29.16
8.7	11/32	2.9	1.46	1.66	2.08	2.49	2.91	3.33	3.74	4.16	4.58	5.00	5.20	36.84
9.6	3/8	3.2	1.77	2.03	2.53	3.04	3.55	4.05	4.56	5.07	5.58	6.07	6.30	44.85
10.5	13/32	3.5	2.12	2.43	3.03	3.64	4.24	4.85	5.58	6.05	6.66	7.28	7.56	53.66
12.0	15/32	4.0	2.77	3.17	3.96	4.75	5.54	6.33	7.12	7.92	8.71	9.51	9.89	70.08
13.5	17/32	4.5	3.50	4.00	5.00	6.01	6.99	8.01	9.00	10.00	11.02	12.02	12.50	88.70
15.0	19/32	5.0	4.33	4.95	6.19	7.42	8.63	9.89	11.10	12.37	13.61	14.84	15.40	109.5