

# 毛眼

## Wire Rope Thimbles

STANDARD THIMBLE



For Rope Diam.		Dimensions ( mm )						Weight
mm	inch	Overall length	Overall Width	Inside Length	Inside Width	Inside Width of Score	Max Pin Dia.	Kg
3	1/8	45.8	24.0	30.2	14.5	4.0	14	0.015
5	3/16	47.5	25.5	31.8	16.0	5.6	15	0.016
6	1/4	49.2	27.0	33.3	17.5	7.1	16	0.017
8	5/16	54.0	31.8	38.1	20.6	9.5	19	0.018
9	3/8	60.3	37.3	41.3	23.8	11.1	22	0.034
13	1/2	69.9	44.5	47.6	28.6	14.3	26	0.085
16	5/8	88.9	60.3	57.2	34.9	17.5	32	0.163
19	3/4	95.3	68.3	63.5	41.3	20.6	38	0.272
22	7/8	127.0	81.0	88.9	47.6	23.8	44	0.408
25	1	144.5	95.3	108.0	63.5	27.0	60	0.476
28	1 1/8 - 1 1/4	158.8	109.5	114.3	69.9	33.3	66	0.753
38	1 1/2	190.5	136.5	127.0	82.6	39.7	79	1.474
44	1 3/4	273.1	184.2	184.2	108.0	47.6	105	2.646
50	2	273.1	184.2	184.2	108.0	54.0	105	2.658



EXTRA HEAVY THIMBLE



For Rope Diam.		Dimensions ( mm )						Weight
mm	inch	Overall length	Overall Width	Inside Length	Inside Width	Overall Thickness	Max Pin Dia.	Kg
6	1/4	55.6	38.1	41.3	22.2	10.3	20	0.034
8	5/16	63.5	46.0	47.6	27.0	12.7	23	0.064
9	3/8	73.0	54.0	54.0	28.6	17.2	26	0.113
11.2	7/16	82.6	60.3	60.3	31.8	19.1	30	0.163
13	1/2	92.1	69.9	69.9	38.1	20.9	36	0.231
14	9/16	92.1	71.4	70.0	38.2	23.6	36	0.233
16	5/8	108.0	79.4	82.6	44.5	25.4	41	0.340
19	3/4	127.0	96.8	95.3	50.8	31.8	47	0.667
22	7/8	139.7	108.0	108.0	57.2	34.9	53	0.839
25	1	155.6	125.4	114.3	63.5	39.7	60	1.323
28	1 1/8 - 1 1/4	177.8	149.2	130.2	73.0	47.6	69	1.739
32	1 1/4 - 1 3/8	228.6	173.0	158.8	82.6	57.2	82	3.704
38	1 3/8 - 1 1/2	230.2	181.0	165.1	88.9	66.7	85	5.292
40	1 5/8	285.6	206.4	203.2	101.6	70.0	98	7.371
44	1 3/4	309.6	215.9	228.6	114.3	73.0	111	8.335
50	1 7/8 - 2	384.2	263.5	304.8	152.4	79.4	149	11.680
56	2 1/4	435.0	301.6	355.6	177.8	92.1	174	17.463

SOLID THIMBLE



For Rope Diam.		Dimensions ( mm )				Weight
mm	inch	Overall length	Overall Width	Thickness	Max Pin Dia.	Kg
13	1/2	71.4	54.0	22.2	25	0.454
16	5/8	119.1	85.7	28.6	30	1.134
19	3/4	119.1	85.7	34.9	34	1.497
22	7/8	154.0	114.3	41.3	41	2.268
25	1	154.0	114.3	46.0	50	2.948
28	1 1/8	184.2	136.5	52.4	57	3.856
32	1 1/4 - 1 3/8	184.2	136.5	58.7	63	4.536