


卸克

Forged Anchor Shackle

SCREW PIN

G-209 S-209



BOLT TYPE

G-2130 S-2130



Size		Dimensions (mm+10%)											S.W.L	Weight
mm	inch	A	B	C	D	E	F	G	H	L	M	P	Ton	Kg
5	3/16	9.7	6.4	22.4	4.8	15.2	14.2	24.9	37.3	4.1	28.4	4.8	1/3	0.05
6.5	1/4	11.9	7.9	28.7	6.4	19.8	15.5	32.5	46.7	4.8	35.1	6.4	1/2	0.12
8	5/16	13.5	9.7	31.0	7.9	21.3	19.1	37.3	53.1	5.6	42.2	7.9	3/4	0.19
9.5	3/8	16.8	11.2	36.6	9.7	26.2	23.1	45.2	63.2	6.4	51.6	9.7	1	0.31
11	7/16	19.1	12.7	42.9	11.2	29.5	26.9	51.6	73.9	7.9	60.5	11.2	1 1/2	0.38
13	1/2	20.6	16.0	47.8	12.7	33.3	30.2	58.7	83.3	9.7	68.3	12.7	2	0.63
16	5/8	26.9	19.1	60.5	16.0	42.9	38.1	74.7	106.4	11.2	84.8	17.5	3 1/4	1.38
19	3/4	31.8	22.4	71.4	19.1	50.8	46.0	88.9	126.2	12.7	100.8	20.6	4 3/4	2.25
22	7/8	36.6	25.4	84.1	22.4	57.9	53.1	102.4	148.1	12.7	114.3	24.6	6 1/2	3.38
25	1	42.9	28.7	95.3	25.4	68.1	60.5	119.1	166.6	14.2	128.8	26.9	8 1/2	5.32
28	1 1/8	46.0	31.8	108.0	29.5	73.9	68.3	131.1	189.7	16.0	142.0	31.8	9 1/2	6.81
32	1 1/4	51.6	35.1	119.1	32.8	82.6	76.2	146.1	209.6	17.5	156.5	35.1	12	9.5
34	1 3/8	57.2	38.1	133.4	36.1	92.2	84.1	162.1	232.7	19.1	173.7	38.1	13 1/2	13.25
38	1 1/2	60.5	41.4	146.1	39.1	98.6	92.2	174.8	254.0	20.6	186.7	41.1	17	17.20
44	1 3/4	73.2	50.8	177.8	46.7	127.0	106.4	225.0	313.4	25.4	230.6	57.2	25	30.38
50	2	82.6	57.2	196.9	52.8	146.1	122.2	253.2	347.5	31.0	262.6	61.0	35	45.00
62	2 1/2	104.9	69.9	266.7	68.8	184.2	144.5	326.9	453.1	35.1	330.2	79.5	55	85.75